

Fire Prevention Division 224 W. 9th Street Sioux Falls, SD 57104

THE OTY OF SOUTH DAKOT

Sioux Falls Fire Rescue

Phone 605-367-8093 Fax 605-367-8138

Fire and Life-Safety Checklist: Nursing Home Occupancies

The following Fire Code requirements are specific for <u>Nursing Home</u> occupancies and should be used as a *supplement* to the "Commercial Business Fire and Life-Safety Checklist".

Fire Safety and Evacuation Plans

- ☐ An approved fire safety and evacuation plan shall be prepared and maintained.
- ☐ Where a fire safety and evacuation plan is required Evacuation Drills shall be conducted six times per year (2 times per year on each shift) 408.5.4
 - □ During emergency evacuation drills, the movement of patients to safe areas or to the exterior of the building is not required.

TABLE 405.2 - FIRE AND EVACUATION DRILL FREQUENCY AND PARTICIPATION

	FREQUENCY	PARTICIPATION
Group I	Quarterly on each shift	Employees

Fire Department Access

- ☐ 3ft clear unobstructed access to fire hydrants and fire protection equipment shall be maintained at all times
- ☐ Fire Department key box shall be installed on all buildings equipped with fire protection systems. [See *Key Box* section in "Commercial Business Fire and Life-Safety Checklist"]
- □ Rooms containing controls for fire detection, suppression or control elements (i.e. airconditioning systems, sprinkler risers and valves) shall be identified for the use of the fire department. Approved signs shall be constructed of durable materials, permanently installed and readily visible. 509.1
- ☐ Where the fire department connection (FDC) is not visible to approaching fire apparatus, the FDC shall be indicated by an approved sign mounted on the street front or on the side of the building. Such sign shall have the letters "FDC" at least 6 inches high and words in letters at least 2 inches high or an arrow to indicate the location. All such signs shall be subject to the approval of the fire code official.
 - ☐ Does the FDC have the required caps in place?

Decorative items

- ☐ The hanging and displaying of decorative materials from acoustical ceiling systems that are part of a fire-resistance-rated floor/ceiling or roof/ceiling assembly shall be prohibited. 703.3
- □ Natural cut trees are not allowed. 806.1.1

involving solid fuels or vegetable or anir fryers (one Class K portable fire extingu	vithin 30 feet of commercial cooking equipment mal oils and fats; or if equipped with deep fat isher of a minimum 1.5 gallon capacity is poking medium capacity of the fryers = 80
	· · · · · · · · · · · · · · · · · · ·
Fire Alarm Systems [See also "Commercial of the An approved fire alarm system shall be	ial Business Fire and Life-Safety Checklist"] installed in all Nursing Home occupancies.
Exiting – Doors, Signs & Aisles [See also ☐ Fire doors cannot be propped open. ☐ Doors with approved delayed egress locativation or loss of power. 1008.1.9.7	"Commercial Business Fire and Life-Safety Checklist"] cks must release upon fire alarm/fire sprinkler
See "Commercial Business Fire and Life-Sa the following: □ Fire Extinguishers □ Commercial Kitchen Hood Systems	☐ Electrical Safety ☐ Housekeeping
 ☐ Fire Sprinklers ☐ Fire Alarms ☐ Exiting – Doors, Signs and Aisles ☐ Exit Signs ☐ Emergency Lighting/Egress Lighting 	 □ Fire Lanes/Fire Hydrants/Fire Department Connections □ Key Boxes (Emergency Fire Department Access Key Boxes)

If you have additional questions concerning fire inspections, please contact us at 367-8093.